

abzar.teb





# Heating Magnetic Stirrer

The entry-level hotplate stirrer for general laboratory applications with aluminun alloy plate



## No-frills laboratory hotplate stirrer

- The aluminum alloy top plate ensures temperature homogeneity and optimum heat transfer across the entire surface
- The SpeedServo<sup>™</sup> counter-reaction technology maintains constant speed as viscosity changes
- Intuitive control panel to set and adjust temperature and stirring speed
- The inclination of the frontal panel is carefully studied to protect the electronics (IP42 protection class)





#### INSTRUMENT - CODE

ARE	230 V / 50-60 Hz	F20500162
ARE	115 V / 60 Hz	F20510162

#### TECHNICAL DATA

	ARE
STIRRING VOLUME (H2O)	Up to 15 liters
ELECTRONIC SPEED REGULATION	Up to 1500 rpm
COUNTER-REACTION	SpeedServo™ Technology
HEATING PLATE	Aluminum alloy
HEATING PLATE DIAMETER	135 mm
ELECTRONIC TEMPERATURE REGULATION	From room temperature to 370 °C
CONSTRUCTION MATERIAL	Epoxy painted aluminum structure
PROTECTION RATING CEI EN 60529	IP 42
STIRRING SYSTEM	High-power driving magnet type "PCM" operated by a mono-phase motor for continuous operation
POWER	630 W
WEIGHT	2.6 Kg (5.7 lb)
DIMENSIONS (WXHXD)	165x115x280 mm (6.5x4.5x11 in)

شركت ابزار طب

تهران، خيابان مطهري، خيابان فجر، يلاك 38











VELP Official Partner





We reserve the right to make technical alterations We do not assume liability for errors in printing, typing or transmission





Via Stazione 16 20865 Usmate (MB) Italy Tel. +39 039 628811

INDIA

### 155 Keyland Court, Bohemia

NY 11716 - U.S. Tel. +1 631 573 6002

Xinlong Rd Building 28, Lane 1333 Shanghai city - China Tel. +86 18017557329

